



STAUFF Push-to-Connect Couplings Series HUS - G1" BSPP Port Complete Coupling

Product Description

STAUFF push-to-connect HUS series couplings consist of a Female body and a Male tip and ensure the assembly of two connecting tube or hose ends can be quickly and easily coupled and uncoupled by hand, without the need of a tool.

Series HUS is made according to the Nordic interchange and available in nominal sizes: 10, 12, 19, 25 (3/8" - 1")

Product Features

- Female and male parts are Zinc-Nickel plated
- Poppet valves available to prevent uncoupled leakage
- Male and female poppet valves fitted standard with decompression valve (pressure eliminator)
- Critical parts are hardened for durability
- Dependable ball-locking mechanism holds the mating halves together
- Female coupling is supplied standard with safety lock ring
- Working Pressure: 260 bar / 3770 PSI

Product Applications

- Heavy road transport equipment
- Construction machinery
- Forestry machinery



Interchange to	TEMA - T Series
	CEJN - 525 Series
	Holmbury - F Series
	DNP PTK1 Series

Item No:

6100199944

Item Designation:

QRC-HUS-25-CC-G16-BT-W3AA

\$55.00 PER SET

RRP: \$140.55 SET = 1 x Male & 1 x Female part

Valid until 31st July 2024 or until stock is sold

Terms and Conditions: For account customers only. All sales are final - special items are not returnable for credit. Subject to GST.