



STAUFF Push-to-Connect Couplings Series IA - G1/2" BSPP Port Complete Coupling

Product Description

STAUFF push-to-connect IA series couplings consist of a Female body and a Male tip and ensure assembly of two connecting tube or hose ends can be quickly and easily coupled and uncoupled by hand, without the need of a tool.

Series IA is made according to **ISO 7241-1, series A** and available in nominal sizes:

06, 10, 12, 19, 25, 38 (1/4" - 1-1/2")

The proven design is suitable for use in Agricultural and Forestry machinery applications. Other applications may, depending on the pressure and flow characteristics, include construction equipment, oil tools, oil equipment, steel mill machinery, and other demanding industrial hydraulic applications.



Product Features

- Zinc-Nickel plated for premium anti-corrosion protection
- Poppet valves prevent uncoupled leakage
- Poppet valves open automatically when coupled within rated working pressure, to keep the flow laminar
- Critical parts are hardened for durability
- Dependable ball-locking mechanism holds the mating halves together
- Socket and plug are precision machined from solid bar stock
- Series IA conforms to the standard of **ISO 7241-1 Series A**

Interchange to	Aeroquip - '5000' series
	Dixon - 'K' series
	DNP - 'PAV1' series
	Faster - 'ANV' series
	Gates - '956' series
	Hansen - 'HA-15000' series
	Parker - '6600' series
	Safeway - 'S56' series
	Stucchi - 'BIR' series
	TEMA - 'TIA' series

Item No:

6100177046

Item Designation:

QRC-IA-12-CC-G08-BT-W3AA

\$15.00 PER SET

RRP: \$44.41 SET = 1 x Male & 1 x Female part

Valid until 31st March 2025 or until stock is sold

Terms and Conditions: For account customers only. All sales are final - special items are not returnable for credit. Subject to GST.